

SOLVENT

Product Codes

TM02, TM 08

Packaging listed overleaf.

Description

Solvent is a synergistic blend of aliphatic and aromatic compounds designed to solvent both polyester and epoxy based products. Solvent may be used as a lubricating trowelling aid to achieve a smooth finish to applied resin based mortars and screeds. Mixing equipment and application tools should always be cleaned with Solvent before setting and hardening has occurred.

Uses include: Obtaining a smooth finish to applied resin based mortars and screeds
Cleaning spillages and snots before hardening has taken place
Cleaning of mixing and application tools

Typical Properties of Solvent

Solvent is based on a blend of Xylene and 1-Methoxypropan-2-ol. This blend acts synergistically to solvent the two main classes of resins used in construction, Polyester and Epoxy.

Solvent is a clear liquid with an aromatic odour. The use of Solvent should always be carried out in a well ventilated area.

Solvent is flammable and no smoking should be allowed in the work area.

Specification Outline

Finishing and cleaning operations should be carried out using Solvent as manufactured by Tecroc products Ltd. The product must be stored and used in accordance with the manufacturer's instructions.

Quality Assurance

Tecroc Products Ltd is a firm of Assessed Capability. The company's quality system conforms to BS EN ISO 9002:1994 and is assessed by SGS Yarsley International Certification Services Ltd.

Instructions For Use

When using Solvent always wear suitable gloves and work in accordance with the health and safety advice given below and in the Safety Data Sheet.

For use as a finishing medium apply a thin coating to application tools such as trowels by means of a dampened cloth. Repeat the coating regularly as the work progresses.

For use as a cleaning up medium apply a more liberal coating to the particular areas involved and work with a cloth to remove the spills.

After use place used cloths into a sealed container for disposal. Details are given in the Safety Data Sheet.

Head Office
Holly Lane Industrial Estate
Atherstone
Warwickshire
CV9 2RN
Tel: 01827 711755
Fax: 01827 711330

Northern Regional Office
Unit 2 Shawcross Court
Shawcross Business Park
Dewsbury
West Yorkshire, WF12 7RF
Tel: 01924 485548
Fax: 01924 488662

Web site: www.tecroc.co.ukE-mail: enquiries@tecroc.co.uk**TECROC**
PRODUCTS

SOLVENT

Storage And Shelf Life

Solvent will have a shelf life of 12 months when kept in moderate ambient conditions. Tins should be tightly closed when not in use. Storage should be in accordance with the Highly Flammable Liquids and Petroleum Gases Regulations 1972.

Packaging And Ordering

Solvent is supplied in screw-capped tins.

5 litre tin Product Code TM02

1 litre tin Product Code TM08

For further information and sales please contact your local Tecroc Products office as listed below.

Precautions

Health and Safety

Solvent is classified under the health and safety legislation CHIP Regulations as "harmful". When used with care, as described in the Safety Data Sheet, Solvent is eminently suitable for site use.

Resin based products and solvents may cause allergic reactions in some people. When using Solvent with resins/hardeners wear gloves, use barrier cream on unprotected skin areas and wear eye protection when mixing, using and cleaning. Ensure adequate ventilation to prevent inhalation of vapours. If skin contact occurs remove resin/hardener immediately with cleansing cream and wash with soap and water. **Do not use Solvent.** Should eye contact occur rinse immediately with plenty of clean water and seek medical advice. If, with resin based products, resin/hardener or Solvent is swallowed do not induce vomiting. Seek medical advice immediately.

Full health and safety data are given in Product Safety Data Sheet.

Fire

Solvent is flammable. Should fire occur extinguish with CO₂ or foam.

Tecroc Products Ltd products are guaranteed against defective materials and manufacture. Products are sold subject to the Tecroc Products Ltd Terms and Conditions of Sale, copies of which are forwarded on invoice and are available on request. Tecroc Products Ltd endeavours to ensure that the above data and any further advice is correct, however, it cannot accept any direct or indirect liability for the use of its products as such usage is beyond its control.

Head Office
Holly Lane Industrial Estate
Atherstone
Warwickshire
CV9 2RN
Tel: 01827 711755
Fax: 01827 711330

Northern Regional Office
Unit 2 Shawcross Court
Shawcross Business Park
Dewsbury
West Yorkshire. WF12 7RF
Tel: 01924 485548
Fax: 01924 488662

Web site: www.tecroc.co.uk

E-mail: enquiries@tecroc.co.uk

TECROC
PRODUCTS